

# Maintainability: Theory and Practice

**NASA ISHEM Forum** 

Napa, California

7 November 2005





# Introduction


- Definition
- Theory
- Metrics
- Practice
- New Directions





# **Definition**

"The relative ease and economy of time and resources with which an item can be retained in or restored to a specified condition when maintenance is performed by personnel having specified skill levels, using prescribed procedures and resources, at each prescribed level of maintenance and repair. In this context, it is a function of design."




**Photo: Courtesy of DoD DefenseLink** 





## **Definition**





# **Definition**

#### Reliability:

The ability of a system or component to perform its required functions under stated conditions for a specified period of time.









# **Definitions**

#### **Mean Time To Repair**

The arithmetic mean of the time required for maintenance actions divided by the number of actions










# Reliability and Maintainability







# **Theory**

- Use and Development of Theory in Maintainability centers around the use of statistics and sampling theory to *predict* aspects of 'ease and economy of resources':
  - Mean Time to Repair
  - Availability
- Mainly used as basis for estimation during system design and development





# **Metrics**

Measure	Description
Mean Time to Repair (MTTR)	The arithmetic average of the maintenance cycle times for the individual maintenance actions of a system (excludes preventive maintenance)
Mean Preventive Maintenance Time	The arithmetic average of the maintenance cycle times for the individual preventive maintenance actions of a system (inspection, calibration, planned replacement, etc)
Median Active Corrective Maintenance Time	The value of corrective maintenance time that divides all downtime values for corrective maintenance so that 50% are equal or greater than the median
Mean Active Maintenance Time	The mean or average <i>elapsed</i> time needed to perform maintenance (both preventive and corrective) excluding logistic and administrative delays
Maximum Active Corrective Maintenance Time	That value of downtime below which one can expect a specified percent of all corrective maintenance to be completed. Must be stated at a given percentile, usually 90 or 95 <sup>th</sup> , primarily related to a lognormal distribution.
Mean Time to Restore System	For highly redundant systems, this is the time need to switch to a redundant backup unit
Mean Down Time	The mean or average time that a system is not operational due to repair or preventive maintenance. This includes logistics and administrative delays.
Maintenance Labor Hours per Hour/Cycle/Action/Month	A measure of labor hours expended, based on operating or calendar time, maintenance actions or operating cycles





# **Metrics**

- Maintenance Information Systems generally record actions by organizations
- Maintainability Metrics are lagging measures from operational databases
  - Often report Symptoms vs Causes
  - Accuracy is Generally Low
  - Completeness (more than 1 Discrepancy?)
- Metrics are used to drive system changes, but improvement comes hard
  - Diffuse responsibilities and actions
  - Platforms develop age related degradation





## **New Directions**

- Maintainability and Reliability are growing in importance to initial design
  - But developing basic design principles for maintainability is still somewhat elusive
  - Adapting "Lean" and "Theory of Constraints" methods has improved execution of legacy systems
- Owner/Operators are driving responsibility for improvement back to OEMs through innovative support methods:
  - Performance Based Logistics
  - Condition Based Maintenance





## **New Directions**

- Technology will be incorporated to improve:
  - Fault Identification and Fault Tolerance
  - Technical Information and Training
  - 'Sense and Respond' Support Actions







